ASTROPHYSICS MEDIUM EXPLORERS (MIDEX) 2021 Announcement of Opportunity (AO) LAUNCH SERVICES INFORMATION SUMMARY

Rev B

NASA-Provided Launch Services Ground Rules/Policy

This document provides additional information for NASA-provided launch services. This launch service will be provided by NASA will be procured and managed by the NASA/Launch Services Program (LSP) using government contracts.

Under this AO, the Proposer may not arrange alternative access to space.

Under the provisions of the NASA Launch Services II (NLS II) contract, the launch service includes the Launch Vehicle (LV) and associated standard services, non-standard services (mission-unique options), all engineering and analysis, and minimum performance standards. LSP also provides technical management of the launch service, technical insight into the LV production/test, coordinates and approves mission-specific integration activities, provides mission unique LV hardware/software development, provides payload-processing accommodations, and manages the launch campaign/countdown.

At the appropriate time following mission selection, LSP will competitively select a launch service provider and award a launch service for the mission based on customer requirements. The launch service is awarded to the Contractor that provides the best value in launch services to meet the Government's requirements based on technical capability/risk, reasonableness of proposed price, and past performance. Accordingly, assumption of a specific launch vehicle configuration as part of the AO proposal will not guarantee that the proposed LV configuration will be selected unless there is firm technical rationale for sole source. Any such rationale should be clearly identified and explained in the proposal.

All NASA-procured launch services will be consistent with NASA Policy Directive (NPD) 8610.7D, NASA Launch Services Risk Mitigation Policy. Launch services acquired by NASA will be managed in accordance with NPD 8610.23C, Launch Vehicle Technical Oversight Policy, and NPD 8610.24C, Launch Services Program (LSP) Pre-Launch Readiness Reviews. These NPDs can be accessed through the AO library.

1

ASTROPHYSICS MEDIUM EXPLORERS (MIDEX) 2021 Announcement of Opportunity (AO) LAUNCH SERVICES INFORMATION SUMMARY

Rev B

<u>Launch Vehicle Information/Configuration/Performance</u>

Three Two scenarios are depicted in this summary, which must be addressed in the proposal (see Requirement 96 in the AO). Any areas that are not compatible with the launch vehicle scenario's capabilities and characteristics must be addressed in the proposal along with any impacts needed to meet these areas (see Requirement 96 in the AO).

Launch Service Costs

The Astrophysics Explorers Program within the Science Mission Directorate will hold the launch service costs. Standard services provided in the launch service costs to be covered by the Astrophysics Explorer Program are:

- the launch vehicle, engineering, analysis, and minimum performance standards and services provided by the NLS II contract in place at the time of LV selection;
- mission integration;
- launch site payload processing;
- range safety support;
- down range telemetry support (launch vehicle only);
- nominal allocation for non-standard/mission unique launch vehicle modifications/services items typically necessary to customize the basic vehicle hardware to meet spacecraft driven requirements (see attachment 2 within this document);

The Baseline launch service for this AO is based upon a medium/intermediate-class vehicle.

The Astrophysics launch service budget set aside for MIDEX 2021 does not include funding for PI/payload-caused launch delays.

Evaluation Criteria

Attachment 3 shows a preliminary Risk Assessment checklist that will be used as a guide for the launch service evaluators during the proposal evaluation phase. This checklist should provide an indication of the types of information that are expected to be in the proposals. If the proposal does not provide sufficient information, the launch vehicle section of the proposal may not be evaluated for full content and may be listed as a finding.

ASTROPHYSICS MEDIUM EXPLORERS (MIDEX) 2021 Announcement of Opportunity (AO) LAUNCH SERVICES INFORMATION SUMMARY

Rev B

NASA Launch Services Program Point of Contact (POC) for Additional Information

Additional information including performance quotes for other orbits/destinations, mission integration inquiries, standard services, and non-standard/mission unique services costs may be obtained from the point of contact below. Other questions must be directed as indicated in the Section 6.1.5 of the AO.

Shaun Daly Mission Manager NASA Launch Services Program Code VA-C Kennedy Space Center, FL 32899

Phone: 321-867-8400

Email: shaun.daly@nasa.gov

Rev B

LV Launch Services Characteristics/Capabilities

Performance Information / Capabilities:

The performance listed for each representative orbit contains the equivalent maximum mass allowed under the standard launch service for the purposes of this AO. Note that other inclinations/altitudes/orbit energies are also available. In some scenarios, an increase in performance may be available, please contact LSP for feasibility.

Table 1 lists some reference orbits/destinations for Scenario 1, with expanded curves provided in Figures 1 and 2. Table 2 lists some reference orbits/destinations for Scenario 2, with expanded curves provided in Figures 3 and 4. Table 3 lists some reference orbits/destinations for Scenario 3, with expanded curves provided in Figures 5 and 6.

Scenario 1:

Reference Orbit		Performance (kg)	Volume
LEO	700 km, Sun-Synch	3385	PLF Scenario 1 (re: Fig. 7)
L2	$C_3 = -0.5 \text{ km}^2/\text{s}^2$	1695	PLF Scenario 1
Lunar	$C_3 = -1.8 \text{ km}^2/\text{s}^2$	1750	PLF Scenario 1

Table 1: Scenario 1 Performance Capability at Reference Orbits




Figure 1: Scenario 1 Representative Performance Capability at Sun-Synchronous Inclination

Rev B




Figure 2: Scenario 1 Representative Performance Capability to High Energy Orbits

Rev B

Scenario 2:

Reference Orbit		Performance (kg)	Volume
LEO	700 km, Sun-Synch	5620	PLF Scenario 2 (re: Fig. 8)
L2	$C_3 = -0.5 \text{ km}^2/\text{s}^2$	1810	PLF Scenario 2
Lunar	$C_3 = -1.8 \text{ km}^2/\text{s}^2$	1925	PLF Scenario 2

Table 2: Scenario 2 Performance Capability at Reference Orbit




Figure 3: Scenario 2 Representative Performance Capability at Sun-Synchronous Inclination

Rev B




Figure 4: Scenario 2 Representative Performance Capability to High Energy Orbits

Performance Ground Rules (valid for all scenarios):

- The LV performance available on NLS-II generally does not include impacts associated with orbital debris compliance; this must be evaluated on a mission-specific basis. Depending on LV design, this could result in a significant performance impact to ensure full compliance with orbital debris policy.
- Guidance reserves have been allocated to account for 3-sigma flight performance.
- Performance is for a Baseline LV configuration; non-standard, mission-unique hardware will require additional assessment.
- Assumes a 47-inch (1194 mm) separation system.
- Mass of entire separation system is book-kept on the launch vehicle side.

Figures 5, 6 and 9 are intentionally omitted from the document.

Rev B

Payload Envelopes:

There are 2 different scenarios for payload fairing volumes allowed under the standard launch service for the purposes of this AO.




Figure 7: Scenario 1 PLF Static Envelope (inches)






Figure 8: Scenario 2 PLF Static Envelope (inches)

Rev B

Launch Vehicle Enveloping Environments:

In the Environments data below, a mass of 1500 kg was used.

Equivalent Sine Environment:

Scenario 1: Covers LEO missions with spacecraft mass < 3385 kg and L2 missions < 1695 kg

Scenario 1 Envelope			
Frequency (Hz)	Axial	Frequency (Hz)	Lateral
5	0.5	5	0.18
10	0.5	10	0.3
12	0.8	20	0.3
16	0.8	30	0.18
18	0.5	50	0.18
30	0.3	65	0.1
100	0.3	100	0.1




Figure 10: Scenario 1 Enveloping Equivalent Sine – Flight Level

Rev B

Scenario 2:

Load Factors cover L2 and Lunar missions with mass < 1800 kg and Low Earth Orbit missions with mass > 1800 kg.

Envelope			
Frequency (Hz)	Axial	Frequency (Hz)	Lateral
5	0.6	5	0.5
20	0.8	80	0.5
35	0.8	80	0.55
35	0.6	85	0.55
75	0.6	85	0.6
75	0.7	100	0.6
78	0.7		
80	0.75		
80	0.9		
100	0.9		




Figure 11: Scenario 2 Enveloping Equivalent Sine – Flight Level

Rev B

CG Loads Factors:

Scenario 1:

Envelope		
Lateral (g's)	Axial (g's) *	*
-1.5	6.5	* positive sign in axial load factor denotes compression
1.5	6.5	factor denotes compression
1.5	-1	
-1.5	-1	
-1.5	6.5	




Figure 12: Scenario 1 Enveloping Design Load Factors (to be applied to CG of Spacecraft)

Attachment 1

Rev B

Scenario 2: Load Factors cover L2 and Lunar missions with mass < 1800 kg and Low Earth Orbit missions with mass > 1800 kg

Envelope		
Lateral (g's)	Axial (g's) *	
1	6	
1	4	
1.5	4	
1.5	3.7	
2 2	3.5	
2	-1.5	
0.6	-1.5	
0.6	-2	
-0.6	-2	
-0.6	-1.5	
-2	-1.5	
-2 -2 -1.5	3.5	
	3.7	
-1.5	4	
-1	4	
-1	6	
1	6	

^{*} positive sign in axial load factor denotes compression




Figure 13: Scenario 2 Enveloping Design Load Factors (to be applied to CG of Spacecraft)

Rev B

Acoustic Environment:

Scenario 1:

Envelope			
Frequency (Hz)	SPL (dB)		
20	122.3		
25	123.8		
31.5	125.5		
40	127.1		
50	128.5		
63	129.7		
80	130.7		
100	131.4		
125	131.7		
160	131.6		
200	131.3		
250	128.9		
315	127.7		
400	126.6		
500	124.8		
630	128.4		
800	128.6		
1000	126.9		
1250	123.1 117.5		
1600 2000	117.5		
2500	113.6		
3150	113.6		
4000	112.5		
5000	111.8		
6300	111.0		
8000	110		
10000	109.1		

Overall SPL (dB) = 141.5

Rev B




Figure 14: Scenario 1 Enveloping Payload Acoustics MPE – 1/3 Octave Band SPL

Rev B

Acoustic Environment:

Scenario 2:

Frequency (Hz)	SPL (dB)
31.5	123.0
40	124.8
50	126.2
63	127.5
80	128.3
100	128.8
125	129.0
160	128.7
200	127.5
250	126.0
315	124.6
400	123.3
500	121.9
630	120.5
800	119.1
1000	117.8
1250	116.4
1600	115.0
2000	113.6
2500	112.3
3150	110.9
4000	109.5
5000	108.1
6300	106.8
8000	105.4
10000	104.0

Overall SPL (dB) = 138.1

Rev B




Figure 15: Scenario 2 Enveloping Payload Acoustics MPE – 1/3 Octave Band SPL

17

Rev B

Shock Environment:

Hz	SRS (g-peak)	
100		100
625		2000
10000		2000




Figure 16: Scenario 1 & 2- Enveloping P95/50 Shock Environment at Separation Plane (LV side)

Note: The provided shock curve is based on LSP experience with separation shock test data of past missions.

18

Rev B

Random Vibe Environment:

Frequency	Max Envelope
20	0.0044
100	0.0044
300	0.01
700	0.01
800	0.03
925	0.03
2000	0.00644
GRMS	5.13




Figure 17: Scenario 2 only- Payload Interface Random Vibration Max Envelope

Rev B

NASA-LSP Standard Launch Services

This list provides an overview of the standard and mission-specific services that the spacecraft customer receives with the NASA-LSP **Baseline** launch service for this AO. If additional services are required but not listed herein, or for any questions, please contact the NASA LSP POC listed in this document.

Integrated Services:

- Range support and services
- Payload processing facility and support
- Contractor Engineering support
- Base Support contractors and logistics
- Hazardous support

Launch Vehicle:

- Launch vehicle that meets customer's performance needs
- Payload Fairing with approximately 2 access doors in standard locations, with thermal and/or acoustic blankets
- Standard LV-provided Payload Separation System
- Standard Payload Adapter
- Standard Test Payload adapter availability
- Spacecraft Spin/De-spin capability for separation (if required)
- Single-Spacecraft Collision/Contamination Avoidance Maneuver (CCAM) capability if needed
- Electrical interface connectors (approximately 3 sets)
- Mission-Unique Reviews (approximately 3)
- Readiness Reviews (approximately 4)
- Risk Management
- Launch Vehicle insight and approval per NPD 8610.23
- Mission integration management & engineering support
- Launch campaign management
- Down range telemetry assets for LV data

Baseline Mission-Unique Services

- Mission-Unique payload isolation system
- T-0 Grade B GN2 or pure air Purge
- ISO 14644-1 Class 7 (Class 10K) integration environment
- Pre-ATP studies such as coupled loads and/or trajectories analysis

Rev B

• Although use of low-level radioactive sources (i.e., with an A2 mission multiple less than 10, as defined in NPR 8715.3, Chapter 6 and Appendix D) is a non-standard service, there is no charge to the PI-Managed Mission Cost, as any charges are minimal (such as radiological storage during payload processing). Note that costs associated with environmental review and launch approval are separate from these activities (reference AO Section 5.2.4).

The following list provides a few examples of non-standard/mission-unique services that are <u>not</u> included in this AO's NASA-provided launch service, and whose cost would need to be included as part of the Principle Investigator-Managed Mission Cost. Contact the LSP POC for further information on these and other non-standard/mission-unique services.

- Custom payload adapters
- Auxiliary Propulsion for target orbit achievement
- Deployable telemetry tracking assets for multiple spacecraft missions
- LV mods/analyses for non-separating interface with multiple SC deployments

Attachment 3

Rev B

Risk Assessment/Evaluation Form Launch Services Program

Proposal Name:					
Proposal #:					
Evaluator POC:					
Phone:					_
Email:					
Launch Service Risk Eva	luation:				
Overall Assessment: - Giv	en the ground rules in	the AO, is th	ne proposed launch v	vehicle (LV)), s	tandard services,
mission-unique services, po	erformance class, costs	and concept	t feasible for this app	olication? (□Ye	es or \square No)
Areas of risk:					
	_	_			
LV Performance: Area of	· ·	ŕ			
Proposed LV configuration					
Proposed Launch Date:					
Launch Period (MM/DD/Y	YYY to MM/DD/YY	YY):	_/to	//	
Launch Window (On any g	given day of the launch	period Minu	ites:Seconds):	:	
Orbit requirements: Apog	ee: km I	Perigee:	km Inclin	nation:	deg.
High Energy requirements:	C3:km ² /sec ²	DLA:	_deg RLA:	deg	
Proposed LV Performance	:				
CBE Mass (including reser	ves) Dry Mass:	kg	Wet Mass:	kg	
NTE Mass (including reser	ves) Dry Mass:	kg	Wet Mass:	kg	
Dry Mass Margin:	kg				
Wet Mass Margin	kg	%			
Formulas: Mass Margin kg = LV Peri Mass Margin % = [(Mass N		_			
LV Performance Comment	s/issues/concerns/risks	::			

Rev B

LV Integration: Area of risk/concern? (Yes or No)
Does the proposer have experience in LV integration? (Yes or No)
LV to Spacecraft Interface: Area of risk/concern? (Yes or No) Proposed Payload Fairing (PLF)
Spacecraft (S/C) Dimensions: Radial: m Height m
Any intrusions outside of the AO Baseline PLF usable STATIC volume? (☐Yes or ☐No)
Are there any special access requirements post-fairing encapsulation? (Yes or No)
If so, list risks:
Mechanical Interface:
Standard Adapter: Custom Adaptor:
Electrical Interface: Are there unique electrical interfaces proposed? (Yes or No)
Standard Pin(s) Connector(s): (Yes or No)
Mission-Unique or Non-Standard Requirements:
Instrument T-0 GN₂ Purge: (☐Yes or ☐No)
T-0 S/C Battery Cooling: (Yes or No)
Planetary Protection Requirements: (Yes or No)
Contamination Control Requirements: PLF: (Yes or No) LV adapter: (Yes or No)
Cleanliness Level: other:
List of Mission-Unique or Non-Standard Services proposed that are not part of the AO Baseline launch service offered:
Unique Facility Requirements: (☐Yes or ☐)
Pad:
S/C Processing Facility:
S/C Environmental Test Plans
Environmental Test Plan/Flow described: (Yes or No)
Test Levels provided: (Yes or No)
Test Schedule provided: (Yes or No)
Comments/issues/concerns/risks:

Rev B

Launch Service Budget Assessment Summary: Area of risk/concern? (Yes or No)
Are the additional Mission-Unique or Non-standard Services, not included in the AO Baseline service, covered by mission flex funding allocated by LSP? (Tyes or No)
If not, list risks:
Has additional funding been identified in the PI-Managed Mission Cost (PI-MMC)? (☐Yes or ☐No) If not, list risks:
Spacecraft Summary Schedule: Area of risk/concern? (Yes or No)
Launch Service Integration time 30+/-3 months? (☐Yes or ☐No)
SC Environmental Test program end date Lmo
Delivery of verified SC loads model delivery to LSP at L-10 months or earlier? (Yes or No)
SC Ship date Lmo
SC to LV integrated operations Ldays
Describe risk of missing the proposed launch date due to spacecraft schedule (environmental testing, launch processing, LV integration):
Missions with Radiological material Area of risk/concern? (Yes or No)
List the Radiological Sources:
Are facilities, not already approved for use, required to store/process the Rad Sources? (Yes or No)
Are any LV modifications not included in the AO Baseline service required for additional safety or Launch approval? (Yes or No)
Other identified cost, technical, schedule risks?: Area of risk? (Yes or No)
List Risks:

END OF DOCUMENT